

## LFB & LFF內徑精度值參考表

單位(unit) : mm

襯套 內徑 ød	外徑 øD		推介 軸承座孔 公差 H7	推介 軸心 公差	壓入後 內徑 公差(參考值) (d)	襯套 內徑 ød	外徑 øD		推介 軸承座孔 公差 H7	推介 軸心 公差	壓入後 內徑 公差(參考值) (d)
	尺寸	公差					尺寸	公差			
3	5	+0.047	+0.012	-0.025 -0.034	+0.062	31	35	+0.090	+0.025 0	-0.025 -0.050	+0.085 0
4	6	+0.017	0	-0.025 -0.037	0	32	36	+0.050			
5	7	+0.055 +0.025	+0.015 0		-0.025 -0.040	+0.065 0	35	39	+0.095	+0.030 0	+0.035 +0.005
6	8			38			42	+0.055			
7	9	+0.060 +0.030	+0.018 0	-0.025 -0.043	+0.068 0	40	44	+0.100 +0.060	+0.035 0	+0.035 0	+0.195 +0.060
8	10					45	50				
9	11	+0.065 +0.035	+0.021 0	-0.025 -0.046	+0.071 0	50	55	+0.110 +0.065	+0.040 0	+0.035 -0.005	+0.200 +0.060
10	12					55	60	+0.120 +0.070			
12	14	+0.070 +0.035	+0.025 0	-0.025 -0.046	+0.081 0	60	65		+0.125 +0.075	+0.040 0	+0.035 -0.005
13	15					65	70	+0.130 +0.075			
14	16	+0.075 +0.040	+0.025 0	-0.025 -0.046	+0.081 0	70	75		+0.140 +0.080	+0.040 0	+0.035 -0.005
15	17					75	80	+0.145 +0.090			
16	18	+0.080 +0.045	+0.025 0	-0.025 -0.046	+0.081 0	80	85		+0.165 +0.100	+0.040 0	+0.035 -0.005
17	19					85	90	+0.185 +0.120			
18	20	+0.085 +0.050	+0.025 0	-0.025 -0.046	+0.081 0	90	95		+0.185 +0.120	+0.040 0	+0.035 -0.005
19	22					100	105	+0.140 +0.080			
20	23	+0.090 +0.050	+0.025 0	-0.025 -0.046	+0.081 0	110	115		+0.145 +0.090	+0.040 0	+0.035 -0.005
22	25					120	125	+0.165 +0.100			
24	27	+0.090 +0.050	+0.025 0	-0.025 -0.046	+0.081 0	130	135		+0.185 +0.120	+0.040 0	+0.035 -0.005
25	28					140	145	+0.185 +0.120			
26	30	+0.090 +0.050	+0.025 0	-0.025 -0.046	+0.081 0	150	155		+0.185 +0.120	+0.040 0	+0.035 -0.005
28	32					160	165	+0.185 +0.120			
30	34	+0.050	0	-0.025 -0.046	+0.081 0						

※本公司其他自潤軸承產品如FTB,STB,DFB等亦適用本表。