


CRSB 外徑攻牙軸心(S45C鍍鉻,不生銹)

Tapped Shaft (Anticorrosive)

材 質：中碳鋼(S45C)
處理方式：表面鍍硬鉻

Material : S45C
Treatment: Ground, Chromium plated and polished



單位(unit) : mm

外徑 Diameter	型號 Type	外徑公差 μm Diameter tolerance	孔距 Pitch	螺栓 Nominal screw	螺牙深度 Thread depth	最大長度 Max length	重量 Weight
D	CRSB	f7	P	M	ℓ	L(max)	kg/m
12	CRSB12	-16	100	M4x0.7	5.5	4,000	0.89
16	CRSB16	-34	150	M5x0.8	7	4,000	1.58
20	CRSB20	-20 -41	150	M6x1	10	4,200	2.47
25	CRSB25		200	M6x1	12	4,200	3.85
30	CRSB30		200	M8x1.25	15	4,200	5.55
35	CRSB35	-25	200	M8x1.25	15	4,200	7.55
40	CRSB40	-50	300	M8x1.25	18	4,200	9.87

Example of identification number:

CRSB 20x1500

① ②

① Type: Shaft diameter

② Overall Length

訂購例 :

CRSB 20x1500

① ②

① 型號：軸心外徑

② 總長度